

## Features and Benefits

- Fully compliant with ExpressCard Specification 1.0
- ExpressCard/34 Form Factor Module
- Compliant with universal serial bus 3.0 specification revision 1.0
- Supports simultaneous operation of multiple USB 3.0/2.0/1.1 devices
- Supports USB data transfer rate of 1.5/12/480/5000 Mbps
- Hot-swapping feature allows users to connect / disconnect devices without powering down the system
- Driver supports for Microsoft Windows 7/Vista/XP/2000/Server 2003 and Server 2008 operation system

## Package Contents

- 1 x USB 3.0 1-Port ExpressCard
- 1 x Driver CD
- 1 x User Manual

## System Requirements

Windows® 7/Vista/XP/2000/Server 2003 and Server 2008  
ExpressCard-enabled system with an available ExpressCard slot

## Hardware Installation

General instructions for installing the card are provided below. Since the design of system may vary, refer to your system's reference manual for further information, if needed. Insert the Serial 1-Port ExpressCard into the ExpressCard slot of your system. Make sure it is inserted all the way in for a solid connection.

## Driver Installation

For Windows® 7/Vista/XP/2000/Server 2003 and Server 2008

1. Please insert the CD driver bound with USB 3.0 1-Port ExpressCard into your CD-ROM Drive.
2. At the Windows desktop click **Start**, then **Run**.
3. Type **D:\Fresco logic\3.0.98.11\_WHQL\309811\_32bit.msi (all 32bit system)**,  
**D:\Fresco logic\3.0.98.11\_WHQL\309811\_64bit.msi (all 64bit system)**  
then click **OK**.  
(Change D: to match your CD-ROM drive letter)
4. follow the on-screen instructions to complete the installation.

## To verify driver installation

Click on the "device manager" tab in system properties, which you access from the windows control panel. you should see a "Fresco Logic xHCI (usb3) Controller" under the "universal serial bus controllers" item.